



Digital Migration Radio PD48X

- Clear Voice
- Built-in Bluetooth & GPS
- Versatile Application





Features

- 
ANALOG & DIGITAL AUTO DETECT
 Compatible with analog conventional and digital conventional modes. Allow PD48X to simultaneously monitor analog and digital modes and automatically respond in each mode. Extremely easy migration to digital from analog.
- 
DTMF SIGNALING
- 
DUAL CAPACITY DIRECT MODE
 In direct mode, you can have two voice calls simultaneously, because of two timeslots from DMR TDMA technology. This feature can be used to increase the radio capacity at no extra costs or frequency license.
- 
PRIVACY
 Basic end-to-end Encryption has your voice and data transmission secured.
- 
EMERGENCY ALARM/CALL
 Emergency Alarm can be sent to other radios via one touch of programmable button, then establish an emergency call in a specific group. Make your response for big event more quickly.
- 
PSEUDO TRUNK
 This virtual trunking feature allocates a free timeslot for urgent communications. This effectively enhances frequency efficiency and allows you to communicate in a timely manner in emergency situations.
- 
REAL TIME CLOCK
 Get a real time displaying on menu and for GPS/text message.
- 
RADIO REGISTRATION SERVICE
 RRS allows PD48X working in Smart Dispatch and Smart One Dispatch, so that the dispatcher can check if the radio is on line or off line.
- 
SUPPLEMENTARY FEATURES*(Optional)*
 PD48X Series provide radio enable/disable, remoter monitor and priority interrupt.
- 
ROAMING*(Optional)*
 Roam from each repeater site to have a non-stop voice transmission.
- 
GPS POSITIONING*(Factory Optional)*
 Built-in GPS module and GPS antenna are designed for outdoor positioning and make it very simple to support different kinds of AVL applications.
- 
BUILT-IN BLUETOOTH*(Factory Optional)*
 Built-in Bluetooth supports PD48X to have wireless audio accessories and other Bluetooth transmission.
- 
RELIABLE AND DURABLE
 PD48X is compliant with MIL-STD-810 G and IP54.
- 
VOX
 This feature allows you to activate the radio microphone via speaking volume, so that free your hands on PTT.

Target Markets



FLEET MANAGEMENT

With RRS, PD48X is allowed to be access to Dispatch application for fleet management. Get what you need for PD48X, like voice dispatch, text message or AVL.



COMMERCIAL

Digital clear voice and loud output audio for most situations with noisy environment in commercial event. With wireless earpiece and text message function, get everything working fine in an easy way.



SECURITY

Privacy in voice and data is the most essential for security guard. Emergency Call, Priority Interrupt, or Remote Monitor function provides a reliable communication.



OUTDOOR ADVENTURES

Quite flexible to quickly program the radio through front panel. Got GPS position in real time. Based on military quality and IP54 water-proof, it is an amazing way to guarantee safety from unexpected event.

Standard



Li-ion Battery
(2000mAh)
BL2010



Belt Clip
BC19



General MCU Rapid-rate Charger
(for Li-Ion/Ni-MH Batteries)
CH10A07



Stubby Antenna



Switching Power Adapter



Hand Strap

Options



Specifications

General		
Frequency Range		UHF: 350-470MHz VHF: 136-174MHz
Channel Capacity		256
Zone Capacity		16
Channel Spacing		25/12.5KHz
Operating Voltage		7.4V
Battery		2000mAh (Li-Ion)
Battery Life (5/5/90)		Analog/Digital: 12/16 hours
Weight		308g
Dimensions		117×55×37mm
Frequency Stability		±0.5ppm
Antenna Impedance		50Ω
Receiver		
Sensitivity (Digital)		0.22μV / BER 5%
Sensitivity (Analog)		0.22μV (Typical) (12dB SIN AD) 0.4μV (20dB SIN AD) 0.22μV (12dB SIN AD)
Adjacent Selectivity	TIA-603	60dB @ 12.5KHz/70dB @ 25KHz
	ETSI	60dB @ 12.5KHz/70dB @ 25KHz
Spurious Response Rejection	TIA-603	70dB @ 12.5/25KHz
	ETSI	70dB @ 12.5/25KHz
Inter-modulation	TIA-603	70dB @ 12.5/25KHz
	ETSI	65dB @ 12.5/25KHz
Hum & Noise		40dB @ 12.5KHz 45dB @ 25KHz
Rated Audio Power Output		0.5W
Rated Audio Distortion		≤3%
Audio Response		+1 ~ -3dB
Conducted Spurious Emission		<-57dBm

Transmitter	
RF Power Output	VHF High power: 5W VHF Low power: 1W UHF High power: 4W UHF Low power: 1W
FM Modulation	11K0F3E @ 12.5KHz 16K0F3E @ 25KHz
4FSK Digital Modulation	12.5KHz Data Only: 7K60FXD 12.5KHz Data & Voice: 7K60FXW
Conducted/Radiated Emission	-36dBm <1GHz, -30dBm >1GHz
Modulation Limiting	±2.5KHz @ 12.5KHz ±5.0KHz @ 25KHz
FM Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
Adjacent Channel Power	60dB @ 12.5KHz, 70dB @25KHz
Audio Response	+1 ~ -3dB
Audio Distortion	≤3%
Digital Vocoder Type	AMBE++
Digital Protocol	ETSI-TS102 361-1,-2,-3
Environmental	
Operating Temperature	-30°C~ +60°C
Storage Temperature	-40°C~ +85°C
ESD	IEC 61000-4-2 (Level 4) ±8kV (Contact) ±15kV (Air)
Dustproof & Waterproof	IP54 Standard
Humidity	Per MIL-STD-810 G Standard
Shock & Vibration	Per MIL-STD-810 G Standard

PD48X, X=0, 2, 5, 6 or 8, model number varies geographically. For details, please contact our regional sales representatives.

All specifications are subject to change without notice due to continuous development.



LEWEL Radiokomunikacja
09-410 Plock, ul. Boryszewska 32
NIP: 7742364853 REGON: 610405992
www.lewel.pl, kontakt@lewel.pl
tel. 243674224, 606223958



Hytera Communications Corporation Limited

Address: Hytera Tower, Hi-Tech Industrial Park North, Beihuan Rd.,
Nanshan District, Shenzhen, China

Tel: +86-755-2697 2999 **Fax:** +86-755-8613 7139 **Post:** 518057

Http: //www.hytera.com **Stock Code:** 002583.SZ



Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, Hytera are registered trademarks of Hytera Communications Co., Ltd.

© 2017 Hytera Communications Co., Ltd. All Rights Reserved.